

EcoClear Hydraulic Oils

ISO GRADES 32, 46, 68

ISO Grade	<u>Typical Properties</u>		
	32	46	68
Color, ASTM D-1500	<0.5	<0.5	<0.5
Appearance	Water Clear	Water Clear	Water Clear
Viscosity, cSt			
At 40 C	31.71	46.5	67.2
At 100 C	5.3	6.8	8.6
Viscosity Index	100	99	98
Flash Point, (COC) Deg F	400	415	425
Pour Point, Deg F	-25	-25	-20
Neut. No., ASTM D 974	0.55	0.55	0.55
Gravity, API @ 60 F	33.1	32.4	31.6
Rust Test, ASTM D 665A/B	No Rust	No Rust	No Rust
Emulsion Test, ASTM D-1401 (40-40-0)	10 Min	10 Min	10 Min
Dielectric Strength, ASTM D-877	35KV	35KV	35KV
Hydraulic Stability, ASTM D-2619			
Cu mass loss, mg/c2	0.13	0.13	0.13
Oxidation Life, ASTM D 943			
Hrs to 2.0 TAN	+15,000	+15,000	+15,000

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

EcoClear Hydraulic Oils have outstanding stability and anti-wear characteristics designed to meet the demanding requirements of most all the major manufacturers and users of hydraulic equipment located in ecologic sensitive areas. These oils are aromatic-free with increased biodegradable and distinguished by their clear appearance and clarity retention in operating systems, good rust protection, low deposit formation, rapid release of entrained air, oxidation resistance, low pour points, and good antifoam properties. All grades comply with requirements of the U.S. EPA LC50 test utilizing marine statistical sampling of mysidopsis-bahia shrimp, rainbow trout, and fathead minnow.

APPLICATIONS

Recommended for critical application of vane and gear pumps operated at elevated pressure levels, i.e. in excess of 6,900 kPa or 1000 psi. For systems incorporating axial piston pumps with pressures in excess of 3500 psi, these oils can be used where the manufacturer specifies anti-wear hydraulic oils. These oils are very effective in reducing pump wear, satisfying lubrication requirements of auxiliary system components, and greatly extending the life of systems operating at high loads, speeds, and temperatures. All ISO Grades comply with requirements of Vickers I-286-S and M-2950-S; Cincinnati Milacron specifications P-68, P69, and P-70. They meet Denison HF-0 and HF-2 requirements. They are suitable for hydraulics operating in the forest industry; dredges, cranes and other hydraulic equipment on off-shore drilling and production facilities. Dielectric strength is warranted at the origin and can be maintained providing low moisture contents are sustained and agitation under humid conditions are minimized.