

PREMIUM POWER STEERING FLUID

Typical Properties

[PS FLUID]

Appearance	Lt. Pale
Flash, COC, Deg F.	360
Pour Point, Deg F.	-40
Viscosity, cSt	
At 40 C.	37.5
At 100 C.	7.26
Viscosity Index	162
Viscosity, Brookfield cP @ -40C	< 64000
Oxidation Stability, D-2272	> 200 minutes
Copper Corrosion	3A Max.

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Premium Power Steering Fluid is formulated from highly refined mixed-base (naphthenic/paraffinic) mineral oils and chemical additives to meet the performance demands of power steering systems. The product is designed to protect power steering systems against pump deterioration by preventing abnormal oxidation, foaming, and wear. The fluid is designed for systems operating over a wide range of temperatures with excellent low temperature properties for cold start steering.

APPLICATIONS

The product provides performance characteristics in accordance with the following specifications:

General Motors	9985010 (SSG 5691754, prior to 12/86 revision) GM Part No. 1050017 Quart / 1052884 Pint Container
Ford	ESW-M2C128-C&D
Chrysler	MS-593, Part No. 4318056
American Motors	AM 4060, 4124
Navistar	TMS 6810
Volkswagen	TL-VM-570-26

Meets service requirements for most other power steering applications and is suitable where automatic transmission fluids are specified. The product is not recommended for Honda power steering systems.