

GAS ENGINE OIL N

[ASHLESS DISPERSANT]

Typical Properties

SAE Grade	30	40	15W-40
Viscosity, cSt			
At 40° C	127	183	106
At 100° C	12.0	14.9	14.5
Viscosity Index	92	92	140
Pour Point, °F	8	12	-20
Flash (COC), °F	440	480	420
Sulfated Ash, %Wt	Nil	Nil	NIL

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Gas Engine Oil "N" is an ashless-dispersant oil that provides engine cleanliness and protects critical engine parts against scuffing and wear. Made with paraffinic base oils and utilizing ashless additive chemistry in its formulation, this product does not contribute to combustion chamber deposits which can cause spark plug fouling and pre-ignition. Additional benefits are realized by those engines that are turbocharged in the form of reduced blade wear, thereby increasing efficiency and decreasing maintenance.

APPLICATIONS

Recommended for all stationary natural gas fueled engines; either 2 or 4 cycle engines in situations where the manufacturer does not specify an ash induced-type oil. The product is typically suggested for use in natural gas fueled engines including those equipped with emission catalysts located at main line natural gas compressor stations and field gathering units.