

**SPECIAL HD 10W-30 MULTIGRADE  
HEAVY-DUTY MOTOR OIL**  
[Meeting API Service Levels CF-4, CG-4, CH-4, CI-4/SJ,SL]

	<u>Typical Properties</u>
SAE Grade, Automotive	10W-30
Viscosity, cSt	
At 40° C	72.4
At 100° C	11.1
Viscosity, SUS	
At 100° F	272
At 210° F	64.4
Viscosity Index	140
Viscosity, CCS, D-5293, -25°C/cP	5800
Flash Point, (COC), °F	415
Pour Point, °F	-30
Sulfated Ash, %wt	1.28
Neutralization No., TBN-E	10.2
HTHS, Vis/cP, D-4683	3.1
Gravity, API @ 60° F	28.5

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

A premium-quality, multigrade crank-case oil for all-season use in commercial mixed-fleet engine operations. The product is manufactured from selected premium quality base stocks, and formulated with the most current V.I. polymer and additive technology to meet performance requirements in all naturally aspirated, turbocharged and supercharged diesel engines as well as all four-cycle gasoline engines. The product reflects API CI-4 test improvements in reducing aeration, better oxidation stability, enhanced soot control, and roller-follower wear limits compared to API CH-4, CG-4.

Special HD 10W-30 meets the following requirements:

API Current Service Classifications CF, CF-4, CG-4, CH-4, CI-4/SJ,SL and obsolete API Classifications CD, CD-II, CE; U.S. Department of Defense Specification MIL-L-46152E (Obsolete) and MIL-L-2104F/A-A-52306A, Mack EO-K/2, EO-L, EO-M, EO-N; Caterpillar TO-2, and Ford M2C144-A & M2C 153-E. The product is suitable for use in engines manufactured by Mack, Caterpillar, Cummins, and all models of Detroit Diesel when there is a preference for multigrade motor oils. For gasoline engines, Special HD 10W-30 is classified API SH/EC, SJ and SL. Suitable for use where Allison C-4 performance is specified.

## APPLICATIONS

Recommended for all major automotive diesel and mixed fleet (diesel/four-cycle gasoline engines) operations in all service and under all operating conditions where the equipment owner specifies the additional performance benefits of multigrade oils of viscosity SAE 10W-30 for both newer and older engines, including newer diesel engines with EGR systems.