PREMIUM TRACTOR HYDRAULIC FLUID

	Typical Properties
SAE Grade	
Automotive	10W-20 (Approx)
Gear	75
Viscosity, cSt	
At 40°C	55
At 100°C	9.2
Viscosity, SUS	
At 100°F	283
At 210°F	57
Viscosity Index	140 (Minimum)
Flash Point, Deg C/(F) (min)	200(392)
Pour Point, Deg C/(F)	-40(-40)
Gravity, API @ 60°F	28.2
Density, lbs/gallon	7.38

The values shown are typical of current production. Some are controlled in the manufacturing process, while other are not. All of them may vary within tolerable ranges.

A high quality, specially designed lubricant containing anti-rust, anti-foam and oxidation inhibitors; plus other additives necessary for the wide range of applications recommended by various tractor manufacturers. The product is an "all-seasonal" type of oil that resists thickening in cold weather and thinning in the heat of summer. It is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition; and provides excellent protection against seal and pump deterioration. Operators, especially farmers, will appreciate the multi-purpose application of Premium Tractor Hydraulic Fluid for transmissions, final drives, and hydraulic systems of tractors thereby eliminating the requirement to stock a variety of oil products.

APPLICATIONS

Formulated and recommended for multipurpose use in transmissions, differentials, hydraulic and power steering units in many different makes of tractors and farm equipment. Premium Tractor Hydraulic Fluid can be used for those hydraulic, wet brake, and transmission applications where the following OEM fluids are recommended:

AGCO: (Deutz-Allis) - PF-821XL, AC-257541AC-272843, International Harvester: B6 (Power Fl. 821) Kubota: UDT Fluid, UDT Super *** Massey Ferguson M-1141 (Permatron III) Allison: C-3, C-4 Case-IH: Hy-Trans, Hy-Trans Plus, Hy Trans Ultra M-1143, M-1145 MAT-3505, MS-1210, MS-1207/1209, JIC-144/145 Minneapolis-Moline: Q-1766, Q-1766B Steiger SEMS 17001** Caterpillar TO-2* & MTO John Deere J20C, J21A, J14B/C Sundstrand HMS 103 ABEX/Dennison HF-0, HF-1, HF-2 (Pumps Only) White Equip. Q-1722 Ford: ESN-M2C41-B, M2C134-D/FNHA-2-C-201.00 White Q 1826 & Type 55 (See AGCO) Hesston/Fiat: AF-87, OT Multi-F Renk Doromat: 874A/B Volvo WB-101/BM Versatile (now New Holland) 23M,24M ZF TE-ML-03E Vickers M-2950-S, I-286-S

- * Premium Tractor Hydraulic Fluid is not recommended for Cat T0-4 service.

 Use Drive Train TC of the appropriate viscosity.
- ** Hydraulic Trans Fluid: Gear, Hydraulic and Wet Brake Oil.
- *** Farm tractor applications only; not for extreme temperatures or severe operations.