

**SYNTHETIC MULTIPURPOSE  
AUTO GEAR LUBRICANT LIMITED SLIP  
SAE GEAR 75W-90, 80W-140  
GL-5, MT-1**

[Extended Life or Severe Application]

Typical Properties

SAE Grade Gear	75W-90	80W-140
Viscosity, cSt		
At 40 C	102.7	207.5
At 100 C	15.5	25.5
Viscosity Index	160	155
Flash Point, (COC) Deg °C(°F)	221(430)	227(440)
Pour Point, Deg °C(°F)	-48(-55)	-46(-50)
Gravity, API @ 60°F	30.0	30.0

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Synthetic Multipurpose Auto Gear Lubricant Limited Slip are designed to provide superb performance for automobiles, light and heavy duty trucks, and various industrial equipment when API Service Classification GL-5 and MT-1 is specified. The products are compounded with synthetic base stocks that have outstanding thermal stability and resistant to high temperature oxidation. The additive system provides extreme pressure characteristics, anti-wear performance, anti-corrosion inhibition, rust prevention, and anti-foaming tendencies.

## APPLICATIONS

Recommended for differentials, rear axles, final drives, conventional manual transmissions, manual steering gears in passenger cars and trucks where API GL-5 type lubricant is specified for severe service and long life. Recommended for gear applications where a controlled sulfur/phosphorus additive package is designated or preferred and extreme cold operating conditions are encountered. Synthetic Automotive Gear Lubricant meets or exceeds API GL-5, DAF, ZF TE-ML 07A, ZF TE-ML 08, GB 13895. Due to refined additive technology and state of the art synthetic base materials that provide significant oxidation resistance, these products may be used to extend drain intervals or used in severe applications.