

PREMIUM (R&O) "HC" TURBINE OILS

ISO GRADES 32, 46, 68, 100

	<u>Typical Properties</u>			
ISO Grade	32	46	68	100
Appearance	<----- Clear/Bright ----->			
Color, ASTM D-1500	<0.5	<0.5	<0.5	<0.5
Viscosity, cSt				
At 40 C	32.0	46.0	68.0	100.0
At 100 C	5.3	6.8	8.4	10.7
Viscosity Index	102	102	101	101
Flash Point, (COC) Deg F	390	415	445	480
Pour Point, Deg F	-25	-15	0	10
Aniline Point, F	223	238	245	256
Turbine Oil Stab. ASTM D-943	8500	8500	8500	8500
Neut. No., TBN-C, ASTM D-974	< 0.11	< 0.11	< 0.11	< 0.12
Sulfur, ppm	<10	<10	<10	<10
Dielectric Properties, ASTM D-877	35K	35K	-	-
Gravity, API @ 60 F	32.0	31.5	31.0	30.6

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

These are premium R & O (rust and oxidation inhibited) oils are zinc free, formulated with HVI paraffinic hydro-processed base stock and selected additives to meet lubrication requirements of various turbine systems, hydraulic applications, and air compressors. The products are characterized by outstanding oxidation stability and provide excellent anti-foam and air release characteristics.

APPLICATIONS

These oils are recommended to meet the requirements of steam turbines, land-based gas turbines, and hydraulic systems where anti-wear characteristics are not a requisite. Other uses include heat transfer systems, gear cases, friction clutches, and other similar industrial applications for long trouble-free service. Premium (R&O) "HC" Turbine Oils have excellent thermal/oxidation stability, rust-prevention, anti-foam, and water separation properties.