

BAR AND CHAIN OIL

ISO Grades: 32, 68, 100, 150

Product Description

Bar and Chain Oil is a lubricant recommended to meet the requirements of the forest products industry under varied operational conditions. The product is manufactured using highly refined base oils to provide oiliness and film strength. It contains a specialized tackiness agent to enhance adherence and minimize oil throw off. This oil can be used in many types of chainsaws using both hand-operated or automatic chain oilers for lubrication of chains, bars, and sprocket assemblies.

Applications

- For lubrication of chains, bars, and sprocket assemblies in chainsaws with hand-operated or automatic chain oilers.

Typical Properties

Property	ISO 32	ISO 68	ISO 100	ISO 150
AGMA Grade	-	2	3	4
Viscosity, cSt @ 40°C	32	65	100	143.7
Viscosity, cSt @ 100°C	4.7	7.8	8.9	10.9
Flash Point (COC), °F(°C)	370(187)	380(193)	400(204)	420(216)
Pour Point, °F(°C)	-10(-23)	+5(-15)	+10(-12)	+15(-10)
Gravity, API @ 60°F	28.5	28.0	25.4	23.3

*The values shown are typical of current production. Some are controlled in the manufacturing process while others are not. All of them may vary within tolerable ranges.