

LOW-TEMP PREMIUM TRACTOR HYDRAULIC FLUID

Product Description

Low-Temp Premium Tractor Hydraulic Fluid is a high-quality, specially designed lubricant containing anti-rust, anti-foam, and oxidation inhibitors, plus other additives necessary for a wide range of applications recommended by various tractor manufacturers.

This low-viscosity oil resists thickening in extreme cold and is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition. It also provides excellent protection against seal and pump deterioration.

Applications

Formulated and recommended for multipurpose use in transmissions, differentials, hydraulic, and power steering units in various tractors and farm equipment requiring low-viscosity fluid with exceptional cold-temperature properties.

This fluid is suitable for applications requiring:

- John Deere J20D
- MS-1207/1209
- JIC-144/145
- Caterpillar T0-2
- ABEX/Dennison HF-0, HF-1, HF-2 (pumps only)
- Vickers 35VQ25

Typical Properties

Property	Value
SAE Grade	Automotive 0W-16 (Approx)
Gear	75
Viscosity, cSt @ 40°C	34.42
Viscosity, cSt @ 100°C	7.1
Viscosity Index	175
Flash Point, °C/°F	180 (356)
Pour Point, °C/°F	-45 (-49)
Gravity, API @ 60°F	28.2
Density, lbs/gallon	7.38

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.